



hot water professional high pressure cleaner

General technical features

- innovative and functional design • pump with 3 ceramic pistons, rod/crank system and brass head • 4 or 2 pole electric motor (1400 or 2800 Rpm), continuous duty with overload thermal switch • elastic coupling between motor and pump (1400rpm models) • delayed auto-stop 20" • burner protection device • water level check • microleakages check • reinforced, acoustic insulated polyethylene made frame and handle (wide thickness), integrated fuel tank and integrated chemical tank , self-extinguishing and 100% recyclable • 24Volt switchboard, ABS, class of insulation IP55, self extinguishing and 100% recyclable. Easy accessibility to the components • 2 wide section fixed wheels (260mm) and 2 revolving braked wheels (100mm) • vertical boilers in stainless steel with separate gas oil pump with efficiency >90% (low fuel consumption) • separate regulation valve with the pump set to zero when the spray gun is closed • security valve • highly sensitive thermostat with direct immersion bulb and constant temperature control • direct feeding with detergent aspiration device in low pressure (high pressure with water tank in optional) with metering system • hose, lance with automatic gun as standard professional accessories (hose reel mt.20 in optional)



rational design, high accessibility for easy maintenance

Modello Model	Giri/m. R.p.m.	Codice Cod.	Pressione Pressure	Portata Flow rate	Motore Motor	Voltaggio Voltage	Dimensioni Dimensions	Peso Weight
			bar / psi	lt./min.-Gpm	hp - kw	volt	cm.	kg.
KON 10.10	2800	000.12.001	100- 1450	10 - 2,60	2,5Hp - 1,8Kw	230 M	92 x 61x 85	95
KON 13.10	2800	000.12.002	130- 1750	10 - 2,60	3Hp - 2,2Kw	230 M	92 x 61x 85	95
KON 15.13	2800	000.12.003	150- 2175	13 - 3,43	5Hp - 3,67Kw	230/400 T	92 x 61x 85	105
KON 10.12	1400	000.12.004	100- 1450	12 - 3,20	3Hp - 2,2Kw	230 M	92 x 61x 85	105
KON 14.10	1400	000.12.005	140- 2030	10 - 2,60	3Hp - 2,2Kw	230 M	92 x 61x 85	105
KON 15.14	1400	000.12.006	150- 2175	14 - 3,70	5,5Hp - 4Kw	230/400 T	92 x 61x 85	105
KON 17.13	1400	000.12.007	170- 2465	13 - 3,43	5,5Hp - 4Kw	230/400 T	92 x 61x 85	105

Standard Equipment:

- * STOP TOTALE RITARDATO / *DELAYED AUTO STOP*
- * CONTROLLO CALDAIA / *BOILER SECURITY*
- * GIUNTO ELASTICO MOTORE-POMPA/ *ELASTIC COUPLING between motor and pump(1400rpm models)*
- * ALIMENTAZIONE DIRETTA (detergente in bassa pressione) / *direct feeding with low pressure chemical*
- * n°1 TUBO/HOSE mt.10 R1
- * n°1 LANCIA / *LANCE* cm.110 + n°1 PISTOLA AUTOMATICA / *AUTOMATIC GUN*
- * n°1 UGELLO-LANCIA / *NOZZLE* + INNESTI RAPIDI / *INLET-OUTLET COUPLINGS*

Optional accessories:

- OK.017 RUBINETTO VAPORE / *STEAM DEVICE*
- OK.070 ANTICALCARE ELETTRONICO / *DISCALING INJECTOR*
- OK.019 VASCHETTA ALIMENTAZIONE (ASPIRAZIONE DETERGENTE IN ALTA PRESSIONE)
WATER TANK KIT (FOR HIGH PRESSURE CHEMICAL SUCTION)
- OK.082.20 KIT AVVOLGITUBO mt.20 COMPLETO DI ACCESSORI PER IL MONTAGGIO (SENZA TUBO)
HOSE REEL mt.20 COMPLETE OF ACCESSORIES OF ASSEMBLING (WITHOUT HOSE)