



**Pompa a 3 pistoni in ceramica, sistema biella/ manovella con testata in ottone. Motore 1400 giri servizio continuo a 4 poli, con protezione termica.**

**Pump with 3 ceramic pump with ceramic pistons (rod/crank system) 4 pole electric motor (1400Rpm), continuous duty with overload thermal switch.**

## IDROPULTRICI AD ALTA PRESSIONE A FREDDO

- Compatta e maneggevole
- Testata ottone
- Trasmissione motore-pompa diretta
- Aspirazione detergente in bassa pressione con dosatore e filtro
- Telaio in acciaio verniciato con polveri epossidiche
- Valvola di regolazione con azzeramento pompa
- Manometro controllo pressione
- Carenatura in materiale plastico rinforzato.

## COLD WATER PROFESSIONAL HIGH PRESSURE CLEANER- EASY TO USE

- Simple and versatile solution
- Brass head
- Motor-pump direct transmission
- Detergent suction in low pressure with metering system and filter
- Steel frame painted with epoxy powders
- Regulation valve with pump set to zero
- Pressure gauge
- Reinforced plastic cover

| Modello<br>Model | Codice<br>Code | Pressione (Bar)<br>Pressure (Bar) |     | Pressione Max<br>Max Pressure |     | Vollaggio<br>Voltage | Potenza<br>Power |     | Peso<br>Weight | Dimensioni<br>Dimensions |
|------------------|----------------|-----------------------------------|-----|-------------------------------|-----|----------------------|------------------|-----|----------------|--------------------------|
|                  |                | NOM                               | MAX | L/MIN                         | L/H |                      | VOLT/HZ/RPM      | KW  |                |                          |
| MEC 100.12       | 10.04.02100    | 100                               | 110 | 12                            | 720 | 230/50/1450          | 2,2              | 3   | 47             | 60x50x78                 |
| MEC 140.10       | 10.04.03200    | 140                               | 150 | 10                            | 600 | 230/50/1450          | 2,2              | 3   | 47             | 60x50x79                 |
| MEC 150.14       | 10.04.01400    | 150                               | 165 | 14                            | 840 | 400/50/1450          | 4                | 5,5 | 48             | 60x50x80                 |
| MEC 150.15       | 10.04.01500    | 150                               | 165 | 15                            | 900 | 400/50/1450          | 4                | 5,5 | 48             | 60x50x80                 |
| MEC 170.13       | 10.04.02300    | 170                               | 180 | 13                            | 780 | 400/50/1450          | 4                | 5,5 | 49             | 60x50x80                 |

### DOTAZIONE STANDARD / STANDARD EQUIPMENT



**1 TUBO PROFESSIONALE R1 DA MT 10**  
**1 R1 10 MT HOSE**



**1 UGELLO-LANCIA**  
**1 HP NOZZLE**



**1 GUN WITH HANDLE**  
**1 LANCE EXTENSION**